

AGROLUX

80-85-90-95-100



PRODUCTIVE AND VERSATILE.

Designed and built to meet a wide range of agricultural requirements, DEUTZ-FAHR Agrolux models are productive and versatile, perfectly capable of taking on the toughest of tillage and general yard duties without difficulty. An advantageous power-to-weight ratio, correct weight distribution and high technical specifications guarantee maximum efficiency under all conditions, while intelligent ergonomics and an intuitive control layout make these machines easy to operate right from the outset.

THE FEATURES

- ▶ SDF Series 1000 Stage I or Stage II engines, 4 cylinders, naturally aspirated or turbo.
- ▶ 12 FWD + 12 REV, 15 FWD + 15 REV or 20 FWD + 20 REV synchronised gearbox.
- ▶ Semi-platform tractor.
- ▶ 30 or 40 km/h maximum speed.
- ▶ Hydrostatic braking on all four wheels.
- ▶ Hydrostatic steering with independent pump.
- ▶ 2WD and 4WD availability.



The central dashboard provides all the essential information.



Neatly arranged control levers in the right console.

AGROLUX		80	85	90	95	100
Engine		SDF 1000.4 W	SDF 1000.4 W	SDF 1000.4 WT	SDF 1000.4 WT	SDF 1000.4 WT
Emissions		Stage II	Stage I	Stage II	Stage I	Stage II
Cylinders/Displacement	n°/cc	4/4000	4/4000	4/4000	4/4000	4/4000
Max. power (2000/25/CE)	kW/HP	54.7/74	62.5/85	64.6/87	68/92	70/96
Lifting capacity	kg	4200	4200	4200	4200	4200
Wheelbase (2WD/4WD)	mm	2340/2360	2340/2360	2340/2360	2340/2360	2340/2360
Max. weight	kg	3100	3100	3200	3200	3200

AGROLUX

50-60-70-4.80-4.80+



EASY TO USE AND TO MAINTAIN.

Featuring compact dimensions and powerful engines, the Agrolux is equipped with everything that a real tractor has to have. With a lifting force of 2,250 kg and 2 PTO speeds, the Agrolux copes even with demanding tasks.



One-piece openable bonnet.



Available also with front 4WD axle with brakes in order to improve safety.

THE FEATURES

- ▶ SDF Series 1000 Stage I or Stage II engines, 3 or 4 cylinders, aspirated or turbo.
- ▶ Fully-synchronized transmission with 12 FWD + 3 REV speeds.
- ▶ PTO with 2 speeds (540/540ECO).
- ▶ Oil-immersed four wheel brakes.
- ▶ Compact construction and low overall height.
- ▶ Platform tractor with folding safety bar.

AGROLUX		50	60	70	4.80	4.80+
Engine		SDF 1000.3 W	SDF 1000.3 W	SDF 1000.3 WT	SDF 1000.4 W	SDF 1000.4 W
Emissions		Stage I	Stage I-II	Stage I-II	Stage I-II	Stage I
Cylinders/Displacement		3/3000	3/3000	3/3000	4/4000	4/4000
Max. power (Stage I)		kW/HP	33/45	40.5/55	49/67	55/75
Max. power (Stage II)		kW/HP	-	40.5/55	51.5/70	54.4/74
Lifting capacity		kg	2250	2250	2250	2250
Wheelbase (4WD/2WD)		mm	1975/2037	1975/2037	1975/2037	2105/2160
Max. weight (4WD/2WD)		kg	2420/2550	2420/2550	2420/2550	2420/2820