



Round Frame Type

AGRIPAK SPRING TINE CULTIVATOR is ideal for General Cultivating, Weeding, Pasture renovating, and preparing Seedbeds. The continual flexing action of the tines shatters the soil breaking up the clods. The Tiller is fully mounted on the tractor by means of category I, I & II three point hitches pins. The spring-loaded tines swing back under breakaway pressure of 163 Kg; pass over the obstruction and return to the working position with out affecting the work depth of the implement.

The Tiller is fitted with 51mm reversible shovels, which are designed for deep penetration. A working depth up to 229 mm is possible in most soils and is simply controlled from the tractor seat.

SPECIFICATIONS:	Models: AG 19S1	Models: AG 19S2	Models: AG 19S3
No. of Tines:	9	11	13
Linkage Category:	I	I & II	I & II
Frame:	Round Steel or Fixed Tubes	Round Steel or Fixed Tubes	Round Steel or Fixed Tubes
Overall Width:	2180 mm	2900 mm	2900 mm
Overall Length:	813 mm	813 mm	813 mm
Tine Spacing:	178 mm / 229 mm	229 mm / 254 mm	229 mm
Overall Height:	1.02 m	1.02 m	1.02 m
Cultivating Width:	1880 mm	2590 mm	2790 mm
Max. Working Depth:	229 mm	229 mm	229 mm
Weight:	209 Kgs	236 Kgs	268 Kgs
Max. Jump Load Settings:	136 - 159 Kgs	136 - 159 Kgs	136 - 159 Kgs
Tractor Compatibility:	25 - 35 Hp	40 - 85 Hp	50 - 85 Hp
Type of Tines:	Spring loaded - 51 mm Reversible Point Shovels		

* All the above models are also available in Heavy Duty Quality Models AG - 19H1, AG - 19H2 and AG - 19H3.
 * Three styles are available; in Round Steel Torsion Tube Model, Round Steel Torsion Tube in Taggle form, and Fixed Steel Model.



Square Frame Type