



AGRIPAK DISC PLOUGH is better used for deep ploughing in root-infested, sticky, stony, and hard soils. Mixes remains of crops and weeds throughout the depth of ploughing hence ideal for rain-fed areas for checking soil erosion by water and wind.

Spring loaded floating rear furrow wheel controls the side draft to ensure straight work and ease of handling by smaller tractor.

- Re-greasable Taper Roller Bearings in- disc hubs.
- Disc angle adjustable to vary the penetration with varying soil conditions.
- Cat I & II linkage.
- Disc Scrapers are adjustable to ensure that the Discs remain clean in all conditions.

| SPECIFICATIONS: | AG 02S | AG 02M | AG 02L |
|-------------------------|----------------------------------|----------------------------------|-------------------------|
| Frame Type: | Tubular Stainless Steel | Tubular Stainless Steel | Tubular Stainless Steel |
| Number of Furrows: | 2, 2 + 1 | 3, 3 + 1 | 3+1 |
| Furrow Width: | 216mm - 267mm | 216 - 267 mm | 260 - 280 mm |
| Max. Working Depth: | 240mm (9.4") | 240 mm | 240 mm |
| Longitudinal Clearance: | 522mm(20.6") | 522 mm | 522 mm |
| Furrow Wheel Diameter: | 510mm (20") | 510 mm | 510 mm |
| Plain Discs: | 660mm (26") or 710mm (28") x 5mm | 660mm (26") or 710mm (28") x 5mm | 6 mm |
| Bearings: | Taper Roller | Taper Roller | Taper Roller |
| Weight: | 276 - 365Kg | 342 - 440Kg. | 400 - 450 Kg |
| Tractor Compatibility: | 35 - 80 Hp | 40 - 80 Hp | 90 & Above Hp |



MF Design
Disc Plough
(2+ Furrows Model)



BALDEN Design
Disc Plough
(3+ Furrows Model)