



In Double Axle and Turning Circle Style



Normal for Farming Use

AGRIPAK FARM HYDRAULIC TRAILER brings easiest way either in farm transportation loading and unloading material as well as provides special facilities in Construction and Road Building work. It provides efficiency and minimum completion timework that made up of Heavy Duty Steel Welded with rigid construction & robust material. Trailer provides a selection of Hydraulic Lifting Capacity Sizes from 8 - 18 Tons.

SPECIFICATIONS:	AG 34S	AG 34M1	AG 34M2	AG 34L1	AG 34L2
Size:	8' x 6' x 2'	10' x 6' x 2'	12' x 6' x 2'	13' x 7' x 2'	14' x 7' x 2'
Bed Sheet Gauge:	SWG 10	SWG 10	SWG 10	SWG 10	SWG 10
Side Sheet Gauge:	SWG 10	SWG 10	SWG 10	SWG 10	SWG 10
Axle Size with J6 HUB:	5" x 8mm	5" x 8mm	5" x 8mm	5" x 8mm	5" x 8mm
Axle Bearing Size:	32.213, 32.216	32.213, 32.216	32.213, 32.216	32.213, 32.216	32.213, 32.216
Frame Channel Size:	8" x 3"	8" x 3"	8" x 3"	8" x 3"	10" x 3"
Cross (Floor) Channel Size:	3" x 1"	3" x 1"	3" x 1"	3" x 1"	3" x 1"
Body Channel Size:	6" x 3"	6" x 3"	6" x 3"	6" x 3"	6" x 3"
Tyre Size:	7.50x16 x 2	8.25.00 x 2	8.00.20 x 4	9.00.20 x 4	9.00.20 x 4
Total Rims:	2	2 (More 2 is Opt.)	4	4	4
Weight (without load):	850 Kg	1500 Kg	1800-1900 kg	2200-2300 Kg	2500 2600 kg
Loading Capacity*:	4 - 5 ton	5 - 8 ton	10 - 12 ton	11 - 12 ton	12 - 13 ton
Tractor Compatibility:	35 - 75 Hp	45 - 85 Hp	45 - 85 Hp	65 - 85 Hp	75 - 100 Hp
Paint:	2 coats of desired shade of antirust paint with Zn Oxide Primer.				

* Depends on Tractor Compatibility.

** Also Available in 10'x6.5'x2', 12'x6.5'x2', 13'x7.5'x2' and 14'x7.5'x4'. We can also manufacture Trolleys as per your special requirements.

