



AGRIPAK Hook-Lift Trailers are designed for containers' operation Loading, Transportation, Unloading by lifting of container. Four types of trailers enables to adjust them to size and total weight of containers. High quality of loading and lifting hydraulic systems makes the trailer reliability. These trailers are recommended where transportation logistic based on containers, especially in those places where motor transport is difficult (marshy fields, forest ways). Used wide size wheels make it possible to work in very hard off-road conditions.

SPECIFICATIONS:

| | | | |
|--|---------|---------|---------|
| Maximum carrying capacity of container (t) | 6 | 12 | 15 |
| Technical maximum speed (km/h) | 40 | 40 | 40 |
| The length of the co-operative container (m) | 3,6/4,6 | 4,1/4,6 | 5,5/6,5 |
| Container lifting angle (°) | 52 | 46 | 52 |
| The maximum length of chassis with container (m) | 5,50 | 6,50 | 8,87 |
| The maximum height of chassis with container (m) | 2,43 | 3,17 | 3,42 |
| The maximum width of chassis with container (m) | 2,08 | 2,55 | 2,55 |
| Horse power demand (KM) | 65-70 | 70-85 | 85-105 |
| Own mass (kg) | 1900 | 2600 | 4000 |
| The standard-suspension of axles | stiff | pandel | pandel |
| Standard size of tyres | 8.25.20 | 8.25.20 | 9.00.20 |
| Oil demand (l) | 17 | 20 | 40 |
| Hydraulic pressure (Mpa) | 18 | 20 | 20 |
| Bogie blocking | Manual | Manual | Manual |
| The standard-diameter of hitch eye (mm) | 40 | 40 | 50 |

AGRIPAK MODELS

| | AG-HLT-36-6 | AG-HLT-36-12 | AG-HLT-36-15 |
|--|-------------|--------------|--------------|
| Maximum carrying capacity of container (t) | 6 | 12 | 15 |
| Technical maximum speed (km/h) | 40 | 40 | 40 |
| The length of the co-operative container (m) | 3,6/4,6 | 4,1/4,6 | 5,5/6,5 |
| Container lifting angle (°) | 52 | 46 | 52 |
| The maximum length of chassis with container (m) | 5,50 | 6,50 | 8,87 |
| The maximum height of chassis with container (m) | 2,43 | 3,17 | 3,42 |
| The maximum width of chassis with container (m) | 2,08 | 2,55 | 2,55 |
| Horse power demand (KM) | 65-70 | 70-85 | 85-105 |
| Own mass (kg) | 1900 | 2600 | 4000 |
| The standard-suspension of axles | stiff | pandel | pandel |
| Standard size of tyres | 8.25.20 | 8.25.20 | 9.00.20 |
| Oil demand (l) | 17 | 20 | 40 |
| Hydraulic pressure (Mpa) | 18 | 20 | 20 |
| Bogie blocking | Manual | Manual | Manual |
| The standard-diameter of hitch eye (mm) | 40 | 40 | 50 |

Standard equipment :

- electric light installation
- side-protective slats
- manual support leg