



SPRAY MACHINE (Blower Sprayer)

AGRIPAK's Blower Sprayer can be used for integrated combat of plagues because of its highly improved performance. The great speed of work permits action at the right time and place, immediately when and where the control is required. It causes less tractor wear and performs more using less power. Only 15HP is required for powerful AGRIPAK's BLOWER SPRAYER to operate as compared to similar equipments. This sprayer can spray 10 hectares an hour after discounting the time spent on tank filling.

SPRAY TANK: Specially designed Fiber Glass Tank is corrosion resistant. Design ensures complete utilization of chemical. 3 way valve permits the filling of tank in just 4 min.

ROTARY ATOMISERS: Each Blade of the three-stage turbine atomizes the chemical to the right size for efficient distribution of spray on plantation. It also houses a special distributor for liquid.

SPECIFICATION:

Net Weight:	250 Kg.
Tank Capacity:	400 Lit.
Filling Aid:	3 Way Valve Enables Quick Filling
Filling Time:	4 Min
Pump Type:	Centrifugal
Spraying Cone:	Up to 40 Meters
Flow Rate Regulation:	By Regulator Valve
Flow Rate:	Ultra Low Volume (ULV) 0.3-1.6 Lit/Min. Low Volume (LV) 10-30 Lit/Min
Working Speed:	3 - 45 Km/Hr.
Droplet Generation:	By Rotary Atomizers



www.tractors.ae

اجري باك للتجارة العامة شركة